

Brand Name of Product	Digital Temperature & Humidity Datalogger
Generic Name of Product	Digital Temperature & Humidity Datalogger
Product Code Number(s)	TEMP-DL-TH
Intended Use	Time, temperature with humidity traceability during transport of temperature/humidity-
	sensitive items.
Range of Applications for Product	
Key specifications of Product	• Very thin and small credit card sized packaging.
	• Compatible with Android phones with NFC chips.

Shipping & Storage	
Shipping Conditions &	
Requirements	
Storage Conditions	
Packaging Conditions	
Shelf Life	

	Instructions for Using Product
Description of Use (s)	To track temperature and humidity.
Preparation for Use	 When you purchase a Temp-DL-TH NFC temperature data logger from Healthmark, your Temp-DL-TH Dashboard account will be setup with administrator rights for your organization by contacting Healthmark at 800-521-6224 Ext. 6634 or email sroehm@hmark.com, 800-521-6224 Ext. 6722 or email sdyrda@hmark.com to set up the organization and the first admin/user. Go to: https://console.tempdlth.com. in the Login Panel, your login will always be your email address and a default password of Temp-DL-TH123.
	TEMP-DL-TH Console
	 As an administrator, you can assign other Temp-DL-TH Dashboard users for your company or user rights by clicking on the Users menu in the left menu panel on the main screen. This is where you will change your own password. The administrator can change the password by clicking on Users in the left panel. Click on the user's email address and change the password and click update to save. Fig. 1



F

Diagrams (drawings, pictures)			
		💯 TEMP-DL-TH Mo 🖤 😫 🗄	
	TEMP-DL-TH		
	Mobile		
	version (.1.) (12)		
	healthmark		
	powered by Healthmark		
	Place your smartphone next to the datalogger	De sou die en de te ile	
		Restart recording	
	Figure 1	Figure 2	
	C C	C C	
		■ 53 19 PM	
	TEMP-DL-TH Scan History	← 🕎 Parameters	
	Settings WiEi settings	Territory settings Language	
	Recover AAR	English	
	GPS status	Temperature unit °C	
		Cloud	
		Server address https://console.tempdlth.com	
		User name healthmark@hmark.com	
	Recording details	Password *****	
	Logger info	BluConsole zone name	
	Restart recording	Auto upload no set	
	Figure 3	Figure 4	
Steps for Use of Product	Using and reading a Temp-DL-T • When logger is profiled for	TH NFC Temperature Data Logge or a manual start, hold the Push butt	er on down for 5 seconds
	to start the logger. The G	reen LCD will flash indicating recon	rding is active.
	 Oreen flashing LED means fee The Red Flashing LED means t 	emperature breach detected (recordi	ing could still be active).
	Programming the NFC Tempera	ture Data Logger with a NFC Mo	bile Device
	1. Bring mobile NFC device to Ter	np-DL-TH NFC logger about 1" aw	vay. When Temp-DL-
	(Fig. 1)	ove moone device away and ornig of	ack to moone device.
	2. Make sure Temp-DL-TH NFC n login and preferences are set in the	nobile App is set-up with your Temp App Settings screen (Fig. 2.)	p-DL-TH Dashboard
	3. Tap the Start New Recording bu	utton. (Fig. 3)	
	4. Choose Profile (Default, Basic of profiles. (Fig. 4.)	or Your Custom) See instructions he	erein on building custom
	5. Tap on the Start New Recording	g button and place mobile device ner	ar Temp-DL-TH NFC
	the product(s) and TAG ID instead	of typing it into the designated space	priori to take a picture of ce.
	6. Temp-DL-TH NFC logger has a Restart Recording button. (Fig. 6)	been programmed. To program ano	ther one, tap on the





F



F

	G ➡ ± ➡ ➡ ➡ ➡ ➡ ■ 9:08 AM		9:58 AM	🖬 🖬 🛨 🌠 🛛 🖓 🕅 💐 🛜 📶 ११% 🗎 8:56 AM
	← 💹 Profile Ma 🖬 🕄 🗄	🗧 💹 Profile Ma 🖬 🕻) :	← 💹 Profile Ma 🖬 🔂 🕴
	Add new profile	Culture Sample	-	culture sample 🔹
	Enter profile name			Tracking number
	Culture <u>Sample</u>		213	ATP
			Δ	
	CANCEL OK			Define profile field
			œ	
			AT M	Tracking number
	Samples Sample Sampler >		A	
	1 2 3 4 5 6 7 8 9 0		V	12345
	qwertyuiop		NZ	CANCEL OK
	asdfghjkl		×	₩
	1 z x c v b n m 🔍		_	
	Sym 🖉 , English(US) . Done		_	
	Figure 4	Figure 5		Figure 6
	4월 ± 🔊 🛱 🖬 🗘 🕅 💐 🛜 ୷ 60% 着 9:54 AM ← 👥 Profile Ma 🖬 🔂 ፤			
	culture sample 👻			
	Product description			
	Tracking number			
	12345			
	culture sample			
	Product description duodenoscope sampling			
	117 Celsius			
	120 Celsius			
	Ralph			
	healthmark@hmark.com			
	Ralph			
	Figure 7			
Interpretation of Results				
Contraindications of Test Results				
Documentation				
Special Warnings and Cautions	The maximum workship tompo	rature range is 22°E to +	158°F (30° C to $\pm 70^{\circ}$ C) with relative
	humidity of 0% to 100%.	auture runge 15 -22 1° 10 +	1.50 1 (-	
Disposal				

Reprocessing Instructions		
Point of Us		
Preparation for Decontamination		
Disassembly Instructions		
Cleaning – Manual		
Cleaning – Automated		
Disinfection		
Drying		
Maintenance, Inspection, and		
Testing		
Reassembly Instructions		

Packaging	
Sterilization	
Storage	
Additional Information	
Related Healthmark Products	
Other Product Support Documents	Proformance [™] Brochure, ProFormance [™] Price List
Reference Documents	
Customer Service Contact	Healthmark Industries Company, Inc
	18600 Malyn Blvd.
	Fraser, MI 48026
	1-586-774-7600
	healthmark@hmark.com
	hmark.com