

Instructions for Use: Steam Sterilization Indicator Dot

Brand Name of Product	Steam Sterilization Indicator Dot			
Generic Name of Product	Steam Indicator Dot			
Product Code Number(s)	CI 140			
Intended Use	The indicators are used to demonstrate the unit or load has been exposed to a steam			
	sterilization process.			
Range of Applications for Product	Demonstrates exposure of load(s) to a steam sterilization process.			
Key Specifications of Product	Type 1 Process Indicator			
	Contains lead			
	Color change: light color (off-white/beige) to dark color (gray/brown/black).			

Shipping & Storage	
Shipping Conditions &	N/A
Requirements	
Storage Conditions	 Best stored in a dry condition at room temperature.
Packaging Contents	N/A
Shelf Life	• Shelf life is four (4) years from the date of manufacture.
	 Lot code and expiration date are printed on the package label.

Instructions for Using Product				
Description of Use(s)	To demonstrate the load has been exposed to a steam sterilization process.			
Preparation for Use	N/A			
Diagrams (drawings, pictures)	N/A			
Steps for Use of Product	 Place in/on item(s) undergoing steam sterilization. Process the load. 			
	 After processing, check the indicator for the specified color change. a. From light color (off-white/beige) to dark color (gray/brown/black): After steam processing, the chemical indicator will show a visual color change 			
Interpretation of Test Results	 After steam processing, the indicator ink should be dark (gray/brown/black). If the indicator ink remains light, it indicates inadequate exposure conditions Item(s) should be returned for reprocessing. After use, the indicator will not change visually when stored in recommended conditions. (Note: The indicator color change is permanent and irreversible.) 			
Contraindications of Test Results	N/A			
Documentation	N/A			
Special Warnings and Cautions	Only for use in steam sterilization.			
	 Do not use to monitor dry heat, ethylene oxide, or other sterilization processes. 			
Disposal	Single use.			

Reprocessing Instructions				
Point of Use	N/A			
Preparation for Decontamination	N/A			
Disassembly Instructions	N/A			
Cleaning – Manual	N/A			
Cleaning – Automated	N/A			
Disinfection	N/A			
Drying	N/A			

Maintenance, Inspection, and	N/A						
Testing							
Reassembly Instructions	N/A						
Packaging	N/A						
Sterilization	Appropriate for use in the following FDA Cleared Steam Sterilization Cycles:						
		Cycle	Temperature	Time			
		Gravity	121 ℃	30 minutes			
		PreVac	132 °C	4 minutes			
		PreVac	135 ℃	3 minutes			
Storage	 Best stored in a dry condition at room temperature. < 50% rh 						
Additional Information	SDS for CI140: http://www.healthmark.info/SterilizationProducts/MSDS/CI 140 SDS.pdf						
Related Healthmark Products	N/A	www.neaitnmark.inio/Ste	rilizationProducts/MSDS/	CI_140_SDS.pdf			
		estian Daalraaina Duaahuu	o Stanilization Doolsooina	Deign List			
Other Product Support Documents Reference Documents	N/A	Sterilization Packaging Brochure, Sterilization Packaging Price List					
Customer Service Contact		1- I 44	T				
Customer Service Contact		mark Industries Company	, inc.				
	18600 Malyn Blvd.						
	Fraser, MI 48026 1-586-774-7600						
	healthmark@hmark.com						
	hmark.com						